



BOSS25

BREAK IN PROCEDURE

You can use 2 3/4", 3" and 1oz or greater.

You need to use at LEAST 1,300 FPS or higher with at least 1oz or a BIGGER / HEAVIER load as it needs to build pressure in the barrel.

If you are using 1,500 FPS or HIGHER be sure to use your high-pressure gas piston.

If you are using BELOW 1,500 FPS use your low-pressure gas piston.

The heavy gas piston will be located in your box. The reason for the FPS suggestion is for the gun to generate enough gas to cycle correctly.

TOP TIPS FOR YOUR CITADEL BOSS25 OPERATION ON NEW SHOTGUNS:

1. Thoroughly clean your new firearm of excess oil within receiver
2. Break your Shotgun in with 50 rounds of ammo - recommended 1450 FPS - 1500 FPS for Break-In
3. Utilize ammunition with 1,300 FPS velocity for the best cycling results
4. Some Magazine Springs are very tight with tension - which can put upward pressure on the round cycling process and cause some cycling issues. We recommend loading mags full and let sit overnight to lighten tension quicker on the mag spring.



Disassembling & Cleaning your BOSS25 - https://www.youtube.com/watch?v=E0LLo-dIF_0
BOSS25 FAQ - <https://www.youtube.com/watch?v=Un1-n3UROJ4&t=1s>